



Hot moulded GRP

Minipol, Maxipol, Combiester and TPD

2019-2020 Edition



CAHORS

CONNECTING ENERGY AND PEOPLE

Since 1969, CAHORS Española is designing and manufacturing polyester enclosures products and solutions for different applications such as gas/water metering, control-command, renewable energies,...

As an original manufacturer and a **very specialist in SMC (Sheet Moulding Compound) moulding**, CAHORS Española is proposing a wide range of GRP enclosures and all necessary accessories to fulfil all your requirements.

CAHORS Española, founded in 1969 and built in its actual shape from 1975, is the oldest subsidiary of Groupe CAHORS, and has today two production sites located in Spain (Figueres and La Roca).

CAHORS Española is composed of 250 people and has an international presence around the world, mainly in Europe, Africa, South America and Asia.



Flash this code
and discover our video
of manufacturing

.....
10
million
boxes sold
throughout the world



.....
4500
tons
of SMC produced
every year
.....



CAHORS, the SMC composite specialist

CAHORS has been using glass-fiber reinforced polyester composite to manufacture its products since the 1970s.

Production of this composite material is possible thanks to **more than 40 years' expertise** in chemical composition, **SMC (Sheet Molding Compound)** manufacture and hot pressing. The resulting composite material, known as SMC, is a type of Glass Reinforced Plastic (GRP).

SMC is **extremely robust in outside environments**. It is **not affected by corrosion** and has good heat resistance, while its glass-fiber reinforced composition means it has excellent resistance to mechanical shocks.

SMC vs. Thermoplastics

Unlike thermoplastics, **SMC does not weaken under the effect of a heat source or melt when exposed to flame, thereby preventing the spread of fire**. SMC also has good resistance to standard solvents as well as alkaline agents.



Double insulation



Resistant to weather conditions



Light



Non-hygroscopic



Resistant to corrosion



Self-extinguishing



Easily machinable



Resistant to impacts

CAHORS

Customized solutions for each application !



Renewable
energies



Distribution
Network



Tertiary
services

Industry



Summary

COMBIESTER system p 06

MINIPOL system p 12

MAXIPOL system p 18


TPD system p 24

DIN system p 26

Customization & Services p 28

References & packaging
information p 30

Street
Lighting



Telecom



Residential



Temporary
installations





COMBIESTER System

MODULAR POLYESTER BOXES (90MM)

Grey color RAL 7035

Also available in Beige, Dark grey or Green. As an option, possibility to paint the enclosure with any color.

Cover fastening

Wide range of cover fastenings with different types of screws: triangular, cross or wing head.



Covers

Available in : transparent, opaque (polycarbonate or polyester) or smoked covers. An opaque polyester cover is also available (some boxes)



From box to enclosure

By means of hinges a box is easily converted to a enclosure.

Threaded inserts

Removable Zamak M6 thread inserts for fixing of the back plates, switchgear, etc.

Polyurethane gasket

All covers are supplied with foamed polyurethane gasket.

Customization

Save assembly costs by requesting our custom build service. Customized base plates manufactured on demand.





Modular : Total Flexibility

The COMBIESTER system is made up of 20 modular boxes, with height and width in multiples of 90 mm.



Can be joined horizontally and vertically using brackets allowing multiple combinations.



Degrees of protection

- **IP66** in individual boxes
- **IP55** in enclosures, according to IEC 60529
- **IK09** according to IEC 62262



Self-extinguishing

to 960° C



UL certification

This range is UL approved. To order your products according to this approval, please contact us.

Depth

Allows to increase the depth of the enclosure to 62.5mm

(except for the enclosure 540x540 which increases the depth to 125mm).




Technical data

Fibreglass reinforced polyester Enclosure (GRP)	RAL-7035 colour	IEC 62208
Double Insulation	Classe II	EN 60439-1
Mechanical (Impact) Resistance	IK09	IEC-62262
Protection against dust-water	IP-66	IEC-60529
Thermal Class	A	UNE-21305
Self extinguishing material	960° C	IEC 60695-2
Temperature Range	-30° +60° C	IEC 60670
Rated Voltage	1000V	IEC 60439-5

Fixing systems

Three options:

- Standard, with internal screw fixing
- External wall mounting brackets
- Pole mounting system









Range of products

BOXES

ACCESSORIES

			135x135	180x135	180x180	270x135	270x180	270x270	270x360
Dimensions (mm)			Height x Width → Depth ↓						
	Polyester box RAL-7035 Transparent polycarbonate cover IP66	129	MH 15 06CCTT15S0	MH 21 06CCTT21S0	MH 22 06CCTT22S0	MH 31 06CCTT31S0	-	-	-
		141	-	-	-	-	MH 32B 06CCTT32B0	-	-
		171	-	-	-	-	MH 32 06CCTT32S0	MH 33 06CCTT33S0	MH 34 06CCTT34S0
		201	-	-	-	-	-	-	MH 34A 06CCTT34A0
	Polyester box RAL-7035 Grey / opaque polycarbonate cover IP66	129	MHO 15 06CCTO15S0	MHO 21 06CCTO21S0	MHO 22 06CCTO22S0	MHO 31 06CCTO31S0	-	-	-
		141	-	-	-	-	MHO 32B 06CCTO32B0	-	-
		171	-	-	-	-	MHO 32 06CCTO32S0	MHO 33 06CCTO33S0	MHO 34 06CCTO34S0
		211	-	-	-	-	-	-	MHO 34A 06CCTO34A0
	Polyester box RAL-7035 Smoked polycarbonate cover Blue screws, RAL-5015 IP66	129	MHF 15 06CCTF15S0	MHF 21 06CCTF21S0	MHF 22 06CCTF22S0	MHF 31 06CCTF31S0	-	-	-
		141	-	-	-	-	MHF 32B 06CCTF32B0	-	-
		171	-	-	-	-	MHF 32 06CCTF32S0	MHF 33 06CCTF33S0	MHF 34 06CCTF34S0
		201	-	-	-	-	-	-	MHF 34A 06CCTF34A0
	Polyester box RAL-7035 Grey, opaque SMC cover IP66	171	-	-	-	-	MHP 32 06CCTP32S0	MHP 33 06CCTP33S0	MHP 34 06CCTP34S0
	Flanges to increase the depth of the boxes. Mounted between base and cover. Height of 62,5 mm 125 mm for 540x540 mm box		-	-	-	-	-	-	06CARP3400
	Self-extinguishable polyester mounting plate		-	06CAPP2100	-	06CAPP3100	06CAPP3200	06CAPP3300	06CAPP3400
	Metal mounting plate		-	06CAPM2100	-	06CAPM3100	06CAPM3200	06CAPM3300	06CAPM3400
	Self-extinguishable bakelite mounting plate		-	06CAPB2100	-	06CAPB3100	06CAPB3200	06CAPB3300	06CAPB3400
	Fuseboard frame		-	-	-	-	06CACM1000	06CACM2000	06CACM3000
	N° of din rails		-	-	-	-	1	2	3
	N° of modules		-	-	-	-	10	20	30

Packaging information. [See p28-35](#)

360x180		360x360		540x270		540x360		540x540		720x360		720x540		
														
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
MH 42 06CCTT42S0	MH 44 06CCTT44S0	MH 63 06CCTT63S0	MH 64 06CCTT64S0	MH 66 06CCTT66S0										
		MH 44A 06CCTT44A0	MH 63A 06CCTT63A0	MH 64A 06CCTT64A0	MH 66A 06CCTT66A0	MH 84A 06CCTT84A0		MH 86A 06CCTT86A0						
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
MHO 42 06CCTO42S0	MHO 44 06CCTO44S0	MHO 63 06CCTO63S0	MHO 64 06CCTO64S0	MHO 66 06CCTO66S0										
		MHO 44A 06CCTO44A0	MHO 63A 06CCTO63A0	MHO 64A 06CCTO64A0	MHO 66A 06CCTO66A0	MHO 84A 06CCTO84A0		MHO 86A 06CCTO86A0						
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
MHF 42 06CCTF42S0	MHF 44 06CCTF44S0	MHF 63 06CCTF63S0	MHF 64 06CCTF64S0	MHF 66 06CCTF66S0										
		MHF 44A 06CCTF44A0	MH 63A 06CCTF63A0	MHF 64A 06CCTF64A0	MHF 66A 06CCTF66A0	MHF 84A 06CCTF84A0		MHF 86A 06CCTO86A0						
-		-		MHP 63 06CCTP63S0	MHP 64 06CCTP64S0	-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-		-		-		
-		-		-		-		-						



Accessories

Screw Cover



Screwdriver (M14)
Grey Ref. 06CATD0100
Blue Ref. 06CATD0200



Manual (M14)
 Ref. 06CATM000



Triangular (M14)
 Ref. 06CATT0100



Safety lock with key (M14)
 Ref. 06CATL0100

Hinges



External hinges
(set of 2)
 Ref. 06CABE0100



Hinge screw
For screwdriver Ref. 06CABM0100
Manual Ref. 06CABD0200




Internal hinges
(set of 2)
 Ref. 06CABI0100

Vent and drain valves



Vent valve
Small size Ref. 06PEAD0001
Big size Ref. 06PEAD0002




Drain valve
 Ref. 06PNAD0002

Fixing systems



Wall mounting
 MH32 → MH86: 06CAFM0100
 MH15 → MH31: 06CAFM0200


Cable sealing boxes



Cable sealing boxes
 A - Ref. 06CACC0100
 B - Ref. 06CACC0200

Enclosure lid with hinged glazed door

270 x 270 x 171 mm Ref. 06CAVP3300
 360 x 270 x 171 mm Ref. 06CAVP3400



Pole mounting
 Ref. 06CAFP0100




Segmented cable sealing boxes
 Ref. 06CABP0100




Cables entry box
 Ref. 0976028

Coupling frames & end plates



Coupling frames	with gasket	06CACA1300	06CACA1800	06CACA2700	06CACA3600
	without gasket	06CACS1300	06CACS1800	06CACS2700	06CACS3600
End plates	with gasket	06CAPF1300	06CAPF1800	06CAPF2700	06CAPF3600
	without gasket	06CAPS1300	06CAPS1800	06CAPS2700	06CAPS3600

Dimensional



Box dimensions (mm)

Mounting plate (mm)

Nom	A	B	C	D	E	F	G	H	I	J	K	L	M
MH 15	135	135	129	115	115	112	113	113	85	85	-	97	97
MH 21	180	135	129	160	115	112	158	113	130	85	-	142	97
MH 22	180	180	129	160	160	112	158	158	130	130	-	142	142
MH 31	270	135	129	250	115	112	248	113	220	86	-	234	98
MH 32b	270	180	141	250	160	124	245	155	200	110	-	220	130
MH 32	270	180	171	250	160	154	245	155	200	110	-	220	130
MH 33	270	270	171	250	250	154	245	245	200	200	-	220	220
MH 34	270	360	171	250	340	154	245	335	200	290	-	220	310
MH 34a	270	360	201	250	340	184	245	335	200	290	-	220	310
MH 42	360	180	171	340	160	154	335	155	290	110	-	310	130
MH 44	360	360	171	340	340	154	335	335	290	290	-	310	310
MH 44a	360	360	201	340	340	184	335	335	290	290	-	310	310
MH 63	540	270	171	515	245	154	515	245	470	200	200	490	220
MH 63a	540	270	201	515	245	184	515	245	470	200	200	490	220
MH 64	540	360	171	515	335	154	515	335	470	290	200	490	310
MH 64a	540	360	201	515	335	184	515	335	470	290	200	490	310
MH 66	540	540	171	515	515	154	515	515	470	470	200	490	490
MH 66a	540	540	201	515	515	184	515	515	470	470	200	490	490
MH 84a	720	360	201	695	335	184	695	335	650	290	290	670	310
MH 86a	720	540	201	695	515	184	695	515	650	470	290	670	490



MINIPOL System

HOT MOULDED ENCLOSURES

Two door types

- **Plain:** allows the mounting of devices in the door.
- **Glazed:** Combined with mounting plate, chassis and/or internal door permits you to see meters, devices, lamps, etc. maintaining the levels of IP and security.

Grey color RAL 7035

Also available in Beige, Dark grey or Green. As an option, possibility to paint the enclosure with any color.

Easy to machine


Vertical patterns in the interior of the doors, which enables the correct fitting of devices.

Easy fitting

Quick fixture guides in the back permits fitting without drilling.

Customization

Custom-made manufacturing.




Locking systems

Different basic closing and locking systems. Customization on request. [See p16](#)

Double bit lock



3-point locking mechanism





Monobloc : all in 1

Product composed of a single block



Self-extinguishing

to 960° C



Degrees of protection

Suited to corrosive environments and climatic agents

- **IP66** according to IEC 60529
- **IK10** according to IEC 62262 (standard)
- **IK08** according to IEC 62262 (glazed window)



UL certification

This range is UL approved. To order your products according to this approval, please contact us.

Security

The chassis and internal door maintain an **IP20** when the external door is open.




Mounting

Pole fixing



Wall mounting



Internal ZAMAK hinge

180° door opening warranted.
ZAMAK standard.
INOX AISI 316 available upon request.



Technical data

Fibreglass reinforced polyester Enclosure (GRP)	RAL7035 colour	IEC 62208
Mechanical (Impact) Resistance	IK10	IEC-62262
Protection against dust-water	IP-66	IEC-60529
Double Insulation	Classe II	EN 60439-1
Corrosion resistance	Yes	IEC 60068-2-30
Thermal Class	A	UNE-21305
Self extinguishing material	960°	IEC 60695-2
Temperature Range	-30° +105°	IEC 60670
Rated Voltage	1.000V	IEC 60439-5



Range of products

300x250x140 400x300x200 400x400x200 500x400x200

ENCLOSURES

ACCESSORIES

Dimensions (mm) Height x Width x Depth						
	Plain door Supplied with 2 double bit lock 3.0 mm IP66		MN 321 06PF320001	MN 432 06PF430001	MN 442 06PF440001	MN 542 06PF540001
	Plain door Three point closing device with swing handle 1 double bit lock 3.0 mm IP66		-	MN 432/3P 06PF430002	MN 442/3P 06PF440002	MN 542/3P 06PF540002
	Glazed door Supplied with 2 double bit lock 3.0 mm IP66		MN 321-V 06PF320002	MN 432-V 06PF430003	MN 442-V 06PF440003	MN 542-V 06PF540003
	Glazed door Three point closing device with swing handle 1 double bit lock 3.0 mm IP66		-	MN 432/3P-V 06PF430004	MN 442/3P-V 06PF440004	MN 542/3P-V 06PF540004
	Polyester mounting plate 4 mm thickness		MN P32 06PFPP0001	MN P43 06PFPP0002	MN P44 06PFPP0003	MN P54 06PFPP0004
	Metal mounting plate Galvanized steel 2 mm thickness		MN PM32 06PFPM0001	MN PM43 06PFPM0002	MN PM44 06PFPM0003	MN PM54 06PFPM0004
	Perforated mounting plate (TELEQUICK) Zinc plated steel Allows quick fixing of devices by using M4, M5 and M6 screw nuts		MN PBR32 06PFPP0001	MN PBR43 06PFPP0002	MN PBR44 06PFPP0003	MN PBR54 06PFPP0004
	Internal door Made of polyester Installation kit included		-	MN PI43 06PFPI0001	MN PI44 06PFPI0002	MN PI54 06PFPI0003
	Chassis for the fitting of modular devices Composed of a chassis, die casta plates and DIN profiles for fixing the devices	N° of modules N° of banks	-	MN CH43 06PFCH0001 24 2x12	MN CH44 06PFCH0002 36 2x18	MN CH54 06PFCH0003 54 3x18
	Die cast plates Knockouts for DIN Switchgear Plates in self-extinguishing insulating material	152 mm height 178 mm height 202 mm height	- - -	- MN CC-300/178 06PFCT0004 - -	MN CC-400/152 06PFCT0001 MN CC-400/178 06PFCT0005 MN CC-400/202 06PFCT0007	MN CC-400/152 06PFCT0001 MN CC-400/178 06PFCT0005 MN CC-400/202 06PFCT0007
	Mounting plate for modular chassis For the fixing of non-modular switchgear Galvanized steel	152 mm height 178 mm height 202 mm height	- - -	- MN PB-300/178 06PFPC0004 - -	MN PB-400/152 06PFPC0001 MN PB-400/178 06PFPC0005 MN PB-400/202 06PFPC0007	MN PB-400/152 06PFPC0001 MN PB-400/178 06PFPC0005 MN PB-400/202 06PFPC0007
	Pole mounting for external, provisional intallations as construction, fairs, street lighting, etc. Steel band not supplied		MN FP-250 06PFFP0006	MN FP-300 06PFFP0007	MN FP-400 06PFFP0008	MN FP-400 06PFFP0008

Packaging information. [See p30-35](#)

600x400x230	600x500x230	600x800x300	800x600x300
MN 642 06PF640001	MN 652 06PF650001	MN 683 06PF680001	MN 863 06PF860001

MN 642/3P 06PF640002	MN 652/3P 06PF650002	MN 683/3P 06PF680002	MN 863/3P 06PF860002
--------------------------------	--------------------------------	--------------------------------	--------------------------------

MN 642-V 06PF640003	MN 652-V 06PF650003	MN 683-V 06PF680003	MN 863-V 06PF860003
-------------------------------	-------------------------------	-------------------------------	-------------------------------

MN 642/3P-V 06PF640004	MN 652/3P-V 06PF650004	MN 683/3P-V 06PF680004	MN 863/3P-V 06PF860004
----------------------------------	----------------------------------	----------------------------------	----------------------------------

MN P64 06PFPP0005	MN P65 06PFPP0006	MN P86-68 06PFPP0007	MN P86-68 06PFPP0007
-----------------------------	-----------------------------	--------------------------------	--------------------------------

MN PM64 06PFPM0005	MN PM65 06PFPM0006	MN PM86-68 06PFPM0007	MN PM86-68 06PFPM0007
------------------------------	------------------------------	---------------------------------	---------------------------------

MN PBR64 06PFPP0005	MN PBR65 06PFPP0006	MN PBR86 06PFPP0008	MN PBR86 06PFPP0007
-------------------------------	-------------------------------	-------------------------------	-------------------------------

MN PI64 06PFPI0004	MN PI65 06PFPI0005	-	MN PI86 06PFPI0006
------------------------------	------------------------------	---	------------------------------

MN CH64 06PFCH0004 54 3x18	MN CH65 06PFCH0005 69 3x23	-	MN CH86/4 06PFCH0006 116 4x29	MN CH86/5 06PFCH0007 145 5x29
--	--	---	---	---

MN CC-400/152 06PFCT0001	MN CC-500/152 06PFCT0002	-	MN CC-600/152 06PFCT0003
MN CC-400/178 06PFCT0005	-	-	MN CC-600/178 06PFCT0006
MN CC-400/202 06PFCT0007	MN CC-500/202 06PFCT0008	-	MN CC-600/202 06PFCT0009


MN PB-400/152 06PFPC0001	MN PB-500/152 06PFPC0002	-	MN PB-600/152 06PFPC0003
MN PB-400/178 06PFPC0005	-	-	MN PB-600/178 06PFPC0006
MN PB-400/202 06PFPC0007	MN PB-500/202 06PFPC0008	-	MN PB-600/202 06PFPC0009

MN FP-400 06PFFP0008	MN FP-500 06PFFP0009	MN FP-800 06PFFP0011	MN FP-600 06PFFP0010
--------------------------------	--------------------------------	--------------------------------	--------------------------------

Mounting plate (mm)


POLYESTER

Ref.	Type	A	B	C	D
06PFP0001	MN P32	213	268	248	175
06PFP0002	MN P43	260	358	338	222
06PFP0003	MN P44	360	358	338	322
06PFP0004	MN P54	360	458	360	322
06PFP0005	MN P64	360	558	538	322
06PFP0006	MN P65	460	558	538	422
06PFP0007	MN P68/86	556	754	734	518




METAL

Ref.	Type	A	B	C	D	E	F
06PFPM0001	MN PM32	213	268	248	175	148	193
06PFPM0002	MN PM43	254	358	338	222	238	234
06PFPM0003	MN PM44	354	358	338	322	238	334
06PFPM0004	MN PM54	354	458	438	322	338	334
06PFPM0005	MN PM64	354	558	538	322	438	334
06PFPM0006	MN PM65	454	558	538	422	438	434
06PFPM0007	MN PM68 MN PM86	550	754	734	518	634	530



PERFORATED

Ref.	Type	A	B	C	D	E	F	G	H
06PFP0001	MN PBR32	202	268	248	175	-	195	200	-
06PFP0002	MN PBR43	250	358	338	222	354	243	240	160
06PFP0003	MN PBR44	350	358	338	322	354	343	240	260
06PFP0004	MN PBR54	350	458	438	322	454	343	340	260
06PFP0005	MN PBR64	350	558	538	322	554	343	440	260
06PFP0006	MN PBR65	450	558	538	422	554	443	440	360
06PFP0007	MN PBR86	545	754	734	518	750	538	636	455
06PFP0008	MN PBR68	754	545	518	734	538	750	455	636



Accessories

Locking systems

All our standard enclosures are supplied with 2 double bit locks 3.0 mm. Order your enclosures with customized locking systems by simply changing the number before the last number of the product reference:

Example : 06PF430031 = enclosure 400mm height x 300mm width x 200mm Depth, manual with key lock

Locks

Wide range of locks adaptables to the enclosures.

*Transform the number before the last one of reference to choose the type of locking device.




Double bit lock
3,0 mm (standard)



Triangular screw
11 mm



Manual
with key lock



Padlock
Inox
Ref. 06PFCR0005
Galvanized steel
Consult us

Ref. accessories	06PFCR0001	06PFCR0002	06PFCR0003
Ref. mounted*	06PFXXX0X	06PFXXX2X	06PFXXX3X

Swing-handle

Wide range of locking devices with swing handle to suit the complete range of enclosures.

Various locks & keys possible (example : 455/405/1242E/421...)



Double bit
lock



Cylinder
& key locked



Without Cylinder
& key



Triangular
11 mm



Triangular 11 mm
+ padlocking handle

Ref. accessories	06PFCR0006	06PFCR0007	06PFCR0008	06PFCR0009	06PFCR0010
Ref. mounted*	06PFxxx0x	06PFxxx7x	06PFxxx8x	06PFxxx9x	06PFxxx10x

Surface mounting

Wall fixing set. Directly to the wall by the means of head-insulated screws.

Set of 4 adjustable brackets



Ref. 06PFAD0001



Ref. 06PFAD0002

Nuts

To fix devices with the help of perforated mounting plate.



Nut M4 Ref. 06PFAD0003
Nut M5 Ref. 06PFAD0004
Nut M6 Ref. 06PFAD0005

Adjustable base plate

Set of four profiles for the adjustment of the base plate, to different depths.
Made of galvanized steel.
Fast fixing to the enclosure.




Enclosure kit for :
MN 432, 442 & 542 Ref. 06PFAD0006
MN 642 & 652 Ref. 06PFAD0007
MN 863 Ref. 06PFAD0008

Ventilation device

To allow ventilation in the enclosure.

(Two air vents must be mounted per enclosure to ensure the correct air circulation)



Little size RAL 7035 x1

Ref. 06PEAD0001

Big size RAL 7035 x2

Ref. 06PEAD0002

IP54 150x150mm x1

Ref. 06PEAD0003



Shutters

Set of shutters enabling partial covering of the window for automatic fuses. Made of a self-extinguishing and isolating material. Fast fixing.



Set of 3 pieces of 1 module and 2 pieces of 1/2 module.

Ref. 06PNAD0001

Drain valve


Enabling drainage of possible condensation. Made of polyester.



For all types of enclosures.

Ref. 06PNAD0002

Dimensional



Enclosure dimensions (mm)

Reference	Type	A (mm)	B	C	D	E	F	G	H	I	J	K	L	M
06PF320001	MN 321	300	250	140	297	248	215	330	-	-	115	220	75	35,5
06PF430001	MN 432	400	300	200	344	338	262	420	158	138	121	281	89,5	53
06PF440001	MN 442	400	400	200	444	338	362	420	158	138	221	281	89,5	53
06PF540001	MN 542	500	400	200	444	438	362	520	158	138	221	381	89,5	53
06PF640001	MN 642	600	400	230	444	538	362	620	187	167	221	481	89,5	53
06PF650001	MN 652	600	500	230	544	538	462	620	187	167	321	481	89,5	53
06PF680001	MN 683	600	800	300	816	558	734	640	257	237	621	481	89,5	53
06PF860001	MN 863	800	600	300	640	734	558	816	257	237	421	681	89,5	53



MAXIPOL System

TOTAL MODULAR POLYESTER CONSTRUCTION

Grey color RAL 7035

Also available in Beige, Dark grey or Green.
As an option, possibility to paint the enclosure with any color.

Type of hinges

Internal hinges allow the door to be opened 105°.

Polyurethane gasket

Preformed and premounted throughout the range.

As an option, possibility to get 180° opening hinges.

Back plate fixing


All models include brackets for fixing the back plate.

Plate support


Allows the fixation plates.
Equipped on all standard enclosures.

Customization

Custom-made manufacturing



Locking systems



3-point locking mechanism operated by swing-handle.
Different profile half cylinder locks. [See p22](#)



Modular : Total flexibility

The enclosure modules can be fitted allowing many different combinations:



Vertical



Horizontal



Back to back

Painted steel custom-made roofs adapted to all your combinations.



Degrees of protection

- **IP55** according to IEC 60529
- **IK10** according to IEC 62262 (standard)
- **IK08** according to IEC 62262 (glazed window)



Self-extinguishing

to 960° C

Top cover modules

- Flat top (**IP55**)
- Rain canopy, front and back ventilation (**IP43 or IP55 on request**)



Two depths

300 and 420 mm.
For electronics,
19" racks,
public lighting,
etc



Technical data

Fibreglass reinforced polyester Enclosure (GRP)	RAL-7035 colour	IEC 62208
Double Insulation	Classe II	IEC-62262
Mechanical (Impact) Resistance	IK10	IEC-60529
Protection against dust-water	IP-55	EN 60439-1
Thermal Class	A	UNE-21305
Self extinguishing material	960° C	IEC 60695-2
Temperature Range	-30° +105° C	IEC 60670
Rated Voltage	1000V	IEC 60439-5

Fixing systems



Wall-mounting



Floor standing



Pole mounting



Range of products

ENCLOSURES

ACCESSORIES



Dimensions (mm)		Height x Width → Depth ↓	500x500	500x750	750x500
		300	MX 553 06PG220001	MX 573 06PG230001	MX 753 06PG320001
		420	MX 554 06PH220001	MX 574 06PH230001	MX 754 06PH320001
	Polyester mounting plate	300 / 420	PMX55 06PGPP0001	PMX57 06PGPP0002	PMX75 06PGPP0003
	Metallic mounting plate	300 / 420	PMMX55 06PGPM0001	PMMX57 06PGPM0002	PMMX75 06PGPM0003
	Galvanised steel frame	300	MA MX3/500 06PGMM0001	MA MX3/750 06PGMM0002	MA MX3/500 06PGMM0001
		420	MA MX4/500 06PHMM0001	MA MX4/750 06PHMM0002	MA MX4/500 06PHMM0001
	Polyester plinth, 60 mm height	300	ZP MX3/500 06PGZP0001	ZP MX3/750 06PGZP0002	ZP MX3/500 06PGZP0001
		420	ZP MX4/500 06PHZP0001	ZP MX4/750 06PHZP0002	ZP MX4/500 06PHZP0001
	Metallic plinth, 85 mm height	300	ZM MX3/500 06PGZM0001	ZM MX3/750 06PGZM0002	ZM MX3/500 06PGZM0001
		420	ZM MX4/500 06PHZM0001	ZM MX4/750 06PHZM0002	ZM MX4/500 06PHZM0001
	Polyester pedestal with hinged door, 500 mm height, to facilitate the fitting and control of cables	300	ZS MX3/500 06PGPS0001	ZS MX3/750 06PGPS0002	ZS MX3/500 06PGPS0001
		420	ZS MX4/500 06PHPS0001	ZS MX4/750 06PHPS0002	ZS MX4/500 06PHPS0001
	Polyester built-in floor pedestal with hinged door, 375 mm height	300	ZE MX3/500 06PGPE0001	ZE MX3/750 06PGPE0002	ZE MX3/500 06PGPE0001
		420	ZE MX4/500 06PHPE0001	ZE MX4/750 06PHPE0002	ZE MX4/500 06PHPE0001
	Floor brackets	300			
		420			
	Pole mounting Order with the corresponding accessory bracket: 06PGAD0001 or 06PGAD0003		06PFFP0012	06PFFP0013	06PFFP0012

Options

Enclosures are also available with:

06PXXXXXX1 → Standard
 06PXXXXXX2 → Bottom opening
 06PXXXXXX3 → Rain canopy
 06PXXXXXX4 → Glazed door

06PXXXXXX5 → Bottom opening + rain canopy
 06PXXXXXX6 → Bottom opening + glazed door
 06PXXXXXX7 → Glazed door + rain canopy
 06PXXXXXX8 → Bottom opening + glazed door + rain canopy



750x750		750x1000*		1000x500	1000x750	1000x1000*	1250x500	1250x750	1250x1000*	1250x1250*
MX 773 06PG330001	MX 7103/2P* 06PG340001	MX 1053 06PG420001	MX 1073 06PG430001	MX 10103/2P* 06PG440001	MX 1253 06PG520001	MX 1273 06PG530001	MX 12103/2P* 06PG540001	MX 12123/2P* 06PG550001		
MX 774 06PH330001	MX 7104/2P* 06PH340001	MX 1054 06PH420001	MX 1074 06PH430001	MX 10104/2P* 06PH440001	MX 1254 06PH520001	MX 1274 06PH530001	MX 12104/2P* 06PH540001	MX 12124/2P* 06PH550001		
PMX77 06PGPP0004	PMX710 06PGPP0005	PMX105 06PGPP0006	PMX107 06PGPP0007	PMX1010 06PGPP0008	PMX125 06PGPP0009	PMX127 06PGPP0010	On request	On request		
PMMX77 06PGPM0004	PMMX710 06PGPM0005	PMMX105 06PGPM0006	PMMX107 06PGPM0007	PMMX1010 06PGPM0008	PMMX125 06PGPM0009	PMMX127 06PGPM0010	On request	On request		
MA MX3/750 06PGMM0002	MA MX3/1000 06PGMM0003	MA MX3/500 06PGMM0001	MA MX3/750 06PGMM0002	MA MX3/1000 06PGMM0003	MA MX3/500 06PGMM0001	MA MX3/750 06PGMM0002	MA MX3/1000 06PGMM0003	MA MX3/1250 06PGMM0004		
MA MX4/750 06PHMM0002	MA MX4/1000 06PHMM0003	MA MX4/500 06PHMM0001	MA MX4/750 06PHMM0002	MA MX4/1000 06PHMM0003	MA MX4/500 06PHMM0001	MA MX4/750 06PHMM0002	MA MX4/1000 06PHMM0003	MA MX4/1250 06PHMM0004		
ZP MX3/750 06PGZP0002	ZP MX3/1000 06PGZP0003	ZP MX3/500 06PGZP0001	ZP MX3/750 06PGZP0002	ZP MX3/1000 06PGZP0003	ZP MX3/500 06PGZP0001	ZP MX3/750 06PGZP0002	ZP MX3/1000 06PGZP0003	ZP MX3/1250 06PGZP0004		
ZP MX4/750 06PHZP0002	ZP MX4/1000 06PHZP0003	ZP MX4/500 06PHZP0001	ZP MX4/750 06PHZP0002	ZP MX4/1000 06PHZP0003	ZP MX4/500 06PHZP0001	ZP MX4/750 06PHZP0002	ZP MX4/1000 06PHZP0003	ZP MX4/1250 06PHZP0004		
ZM MX3/750 06PGZM0002	ZM MX3/1000 06PGZM0003	ZM MX3/500 06PGZM0001	ZM MX3/750 06PGZM0002	ZM MX3/1000 06PGZM0003	ZM MX3/500 06PGZM0001	ZM MX3/750 06PGZM0002	ZM MX3/1000 06PGZM0003	ZM MX3/1250 06PGZM0004		
ZM MX4/750 06PHZM0002	ZM MX4/1000 06PHZM0003	ZM MX4/500 06PHZM0001	ZM MX4/750 06PHZM0002	ZM MX4/1000 06PHZM0003	ZM MX4/500 06PHZM0001	ZM MX4/750 06PHZM0002	ZM MX4/1000 06PHZM0003	ZM MX4/1250 06PHZM0004		
ZS MX3/750 06PGPS0002	ZS MX3/1000 06PGPS0003	ZS MX3/500 06PGPS0001	ZS MX3/750 06PGPS0002	ZS MX3/1000 06PGPS0003	ZS MX3/500 06PGPS0001	ZS MX3/750 06PGPS0002	ZS MX3/1000 06PGPS0003	ZS MX3/1250 06PGPS0004		
ZS MX4/750 06PHPS0002	ZS MX4/1000 06PHPS0003	ZS MX4/500 06PHPS0001	ZS MX4/750 06PHPS0002	ZS MX4/1000 06PHPS0003	ZS MX4/500 06PHPS0001	ZS MX4/750 06PHPS0002	ZS MX4/1000 06PHPS0003	ZS MX4/1250 06PHPS0004		
ZE MX3/750 06PGPE0002	ZE MX3/1000 06PGPE0003	ZE MX3/500 06PGPE0001	ZE MX3/750 06PGPE0002	ZE MX3/1000 06PGPE0003	ZE MX3/500 06PGPE0001	ZE MX3/750 06PGPE0002	ZE MX3/1000 06PGPE0003	ZE MX3/1250 06PGPE0004		
ZE MX4/750 06PHPE0002	ZE MX4/1000 06PHPE0003	ZE MX4/500 06PHPE0001	ZE MX4/750 06PHPE0002	ZE MX4/1000 06PHPE0003	ZE MX4/500 06PHPE0001	ZE MX4/750 06PHPE0002	ZE MX4/1000 06PHPE0003	ZE MX4/1250 06PHPE0004		
MX3 CF 06PGEF0001		(Set of 2 pieces)								
MX4 CF 06PHEF0001		(Set of 2 pieces)								

06PFFP0013

-

06PFFP0012

06PFFP0013

-

06PFFP0012

06PFFP0013

-

-



Example :

06PG230043 = enclosure 500mm height x 750mm width x 300mm depth, triangular 11mm lock and rain canopy.

* Two door enclosures are supplied with a central doorpost piece.
On request it can be fixed, removable or integrated.

Packaging information. See p30-35

Accessories

Locking systems

All our standard enclosures are supplied with 2 double bit locks 3.0 mm. Order your enclosures with customized locking systems by simply changing the number before the last number of the product reference:

Example : 06PG2300**43** = enclosure 500mm height x 750mm width x 300mm depth, triangular 11mm lock and rain canopy

Swing-handle

Wide range of locking devices with swing handle to suit the complete range of enclosures.

*Transform the number before the last one of reference to choose the type of locking device.



Double bit lock



Cylinder & key locked



Without Cylinder & key



Triangular 11 mm



Triangular 11 mm + padlocking handle

Ref. accessories	06PGCR0001	06PGCR0002	06PGCR0003	06PGCR0004	06PGCR0005
Ref. mounted*	06PXXXXX0X	06PXXXXX2X	06PXXXXX3X	06PXXXXX4X	06PXXXXX5X

Wall fixing lugs (Set of 4 pieces)

For standard enclosures
& for enclosures with rain canopy:



Galvanized (standard) :
Ref. 06PGAD0001

Galvanized (with rain canopy) :
Ref. 06PGAD0003

Door stop

Maximum door opening angle 105°.




Ref. 06PGAD0005

Ventilation device

To allow ventilation in the enclosure.
Made of polyester.
(Two air vents must be mounted per enclosure to ensure the correct air circulation)



Device RAL 7035
Ref. 06PEAD0002



IP54 device 150x150mm
Ref. 06PEAD0003



Document pocket

Self-adhesive.



Ref. 06PGAD0006

Step slides


Set of 4 step slides with brackets allowing continuous depth adjustment of the mounting plate.:

For enclosures 300 mm depth:
Ref. 06PGAD0007

For enclosures 420 mm depth:
Ref. 06PHAD0001



Dimensional



Enclosure dimensions (mm)

Mounting plate (mm)

Designation	A	a	B	b	C	c	D	E	F	G
MX 553 / MX 554	510	412	500	405	312/420	274/382	605	375	393	405
MX 573 / MX 574	510	412	750	655	312/420	274/382	855	625	393	655
MX 753 / MX 754	760	662	500	405	312/420	274/382	605	375	643	405
MX 773 / MX 774	760	662	750	655	312/420	274/382	855	625	643	655
MX 7103/2P / MX 7104/2P	760	662	1000	905	312/420	274/382	1105	875	643	905
MX 1053 / MX 1054	1010	912	500	405	312/420	274/382	855	375	893	405
MX 1073 / MX 1074	1010	912	750	655	312/420	274/382	855	625	893	655
MX 10103/2P / MX 10104/2P	1010	912	1000	905	312/420	274/382	1005	875	893	905
MX 1253 / MX 1254	1260	1162	500	405	312/420	274/382	605	375	1143	405
MX 1273 / MX 1274	1260	1162	750	655	312/420	274/382	855	625	1143	655
MX 12103/2P / MX 12104/2P	1260	1162	1000	905	312/420	274/382	1105	875	1143	905
MX 12123/2P / MX 12124/2P	1260	1162	1250	1155	312/420	274/382	1305	1125	1143	1155



TPD System

COST EFFECTIVE POLYESTER ENCLOSURES

Grey color RAL 7035

Type of hinges

Removable internal hinges allow the door to be opened 180°.



Roof

Roof with natural ventilation provided for the whole range.

Plate Support

Allows the fixation of plates.
Equipped on all standard enclosures.




3-point locking mechanism operated by swing-handle.
Different profile half cylinder locks.

Customization

Save assembly costs by requesting our custom build service.
Customized base plates manufactured on demand.



Locking systems





Degrees of protection

- **IP43** according to IEC 60529
- **IK10** according to IEC 62262



Self-extinguishing

to 850° C

Range of products

These GRP range of enclosures have been designed to offer a maximum of flexibility for the integration of components and be adapted to all types of fixtures.

Enclosures dimensions (mm)	Height x Width → Depth ↓	535x535	535x750	790x750	1040x535	1040x750
	310	TPD 55 0472010	TPD 57 0472011	TPD 77 0472012	TPD 105 0472013	TPD 107 0472014

Packaging information. [See p30-35](#)

Mounting plates (mm)

Reference	H x W x D
0976830-ST	410x410x4
0976835-ST	410x660x4
0976873-ST	660x660x4
0976840-ST	900x410x4
0976418-ST	900x660x4



Technical data

Fibreglass reinforced polyester Enclosure (GRP)	RAL-7035 colour	IEC 62208
Double Insulation	Classe II	EN 60439-1
Mechanical (Impact) Resistance	IK10	IEC-62262
Protection against dust-water	IP-43	IEC-60529
Self extinguishing material	850° C	IEC 60695-2
Temperature Range	-30° +105° C	IEC 60670
Rated Voltage	1000V	IEC 60439-5


Accessories



Ventilation device
Ref. 0976056



Wall-mounting brackets
Ref. 0947194



Padlock
Ref. 0947036



DIN System

POLYESTER ENCLOSURES



Reference	Designation	Size (H x W x D)	Ref. enclosure	Ref. pedestal
0472419	DIN 00	1755 x 455 x 320	0472419-C	0472419-Z
0472420	DIN 0	1755 x 590 x 320	0472420-C	0472420-Z
0472421	DIN 1	1755 x 785 x 320	0472421-C	0472421-Z
0472422	DIN 2	1755 x 1115 x 320	0472422-C	0472422-Z

- admit up: 4 BTVC/BTVA NH1-2-3 (100 mm between BTV's) and 3 BTVC/BTVA NH1-2-3 (120 mm) DIN 0,
- admit up: 5 BTVC/BTVA NH1-2-3 (100 mm between BTV's) and 4 BTVC/BTVA NH1-2-3 (120 mm) DIN 1,
- admit up: 7 BTVC/BTVA NH1-2-3 (100 mm between BTV's) and 6 BTVC/BTVA NH1-2-3 (120 mm) DIN 2,
- admit up: 10 BTVC/BTVA NH1-2-3 (100 mm between BTV's) and 9 BTVC/BTVA NH1-2-3 (120 mm)




Degrees of protection

- **IP44** according to IEC 60529
- **IK00** according to IEC 62262



Self-extinguishing

to 850° C



Enclosure		Pedestal	
Reference	Size (E x W x D) mm	Reference	Size (P x W x D) mm
0472419-C	855 x 455 x 320	0472419-Z	900 x 455 x 320
0472420-C	855 x 590 x 320	0472420-Z	900 x 590 x 320
0472421-C	855 x 785 x 320	0472421-Z	900 x 785 x 320
0472422-C	855 x 1115 x 320	0472422-Z	900 x 1115 x 320

In addition to the supply of DIN enclosures, we manufacture a wide range of DIN fuses-way.
Please refer to our dedicated catalogue



Technical data

Fibreglass reinforced polyester Enclosure (GRP)	RAL-7035 (optional in 7032)	IEC 62208
Double Insulation	Classe II	EN 60439-1
Mechanical (Impact) Resistance	IK00	IEC-62262
Protection against dust-water	IP-44	IEC-60529
Self extinguishing material	850° C	IEC 60695-2
Temperature Range	-30° +105° C	IEC 60670
Rated Voltage	1000V	IEC 60439-5

Accessories



Ventilation device
Ref. 0976056



Document pocket
Ref. 0947194



Customization capacity and services

Our catalogue offers a wide range of empty enclosures for all types of applications in various sectors : industry, distribution networks, tertiary...

To meet the needs of our customers, we have a dedicated department proposing the following services:

> PAINTING ENCLOSURES

On specific requests we can realize any specific coating and painting for all our enclosures ranges.
Please, consult us for this optional service.



> CUSTOM-MADE ENCLOSURES FOLLOWING YOUR TECHNICAL DRAWINGS

All our enclosures have been designed and developed to be used for many applications. The enclosures can be equipped with different accessories, cable glands, ventilation valves and fixation systems for any type of equipment.

We realize the full customization depending on your needs and requirements.



> THE CUSTOMIZATION OF YOUR MOUNTING PLATES

The metal or polyester mounting plates allow to mount any type of equipment inside the enclosures. We manage the different holes for easy assembly of your equipment inside the enclosures.



> A WIDE RANGE OF ACCESSORIES AND EQUIPMENT

We are a major player in electrical distribution equipment, we design and manufacture a wide range of accessories and equipment to be integrated inside our enclosures according to your needs.

We can provide you with a full range of equipment and solutions.



Fuse holder solutions 22x58, T00,T1,T2,T3 with or without protection IP2X



Cable glands



Lead terminals for sections 6-240²
copper and aluminum




DIN fuse ways

> OUR CAPACITY TO OFFER FULLY EQUIPPED CUSTOMIZED ENCLOSURES

Our industrial capacity allows us to propose fully prewired and equipped solutions.


As well, we can study your metallic enclosure projects and offer you any type of metallic enclosure on specific request.




> R&D DEPARTMENT READY TO ASSIST YOU ON ANY SPECIFIC PROJECT

We bring our expertise, our R&D tools and certifications to assist you in developing new solutions.

Please send us your requirements including technical specifications, data sheets and we will provide you with a customized offer.



Technical drawing project based



References & packaging information

COMBIESTER range



Reference	Designation	Packing dimensions	Unitary weight (kg)	Pallet		Page
				Quantity	Size	
06CCTT15S0	MH 15	546x286x145	0,35	528	1200x800x2168	8
06CCTT21S0	MH 21	550x375x145	0,44	448	1200x800x2168	8
06CCTT22S0	MH 22	550x375x145	0,50	336	1200x800x2168	8
06CCTT31S0	MH 31	546x286x145	0,58	264	1200x800x2168	8
06CCTT32B0	MH 32-B	550x375x191	1,18	160	1200x800x2048	8
06CCTT32S0	MH 32	550x375x191	1,27	160	1200x800x2048	8
06CCTT33S0	MH 33	555x550x185	1,64	112	1200x800x2173	8
06CCTT34S0	MH 34	550x375x191	1,98	80	1200x800x2048	8
06CCTT34A0	MH 34-A	730x548x215	2,03	72	1200x800x2073	8
06CCTT42S0	MH 42	730x375x191	1,31	120	1200x800x2048	9
06CCTT44S0	MH 44	730x375x191	2,42	60	1200x800x2048	9
06CCTT44A0	MH 44-A	730x375x215	2,56	54	1200x800x2073	9
06CCTT63S0	MH 63	555x550x185	2,67	56	1200x800x2173	9
06CCTT63A0	MH 63-A	555x550x215	2,96	48	1200x800x2073	9
06CCTT64S0	MH 64	550x375x191	3,62	40	1200x800x2048	9
06CCTT64A0	MH 64-A	730x548x215	3,75	36	1200x800x2073	9
06CCTT66S0	MH 66	555x550x185	5,21	28	1200x800x2173	9
06CCTT66A0	MH 66-A	555x550x215	5,44	24	1200x800x2073	9
06CCTT84A0	MH 84-A	730x375x215	4,15	27	1200x800x2073	9
06CCTT86A0	MH 86-A	730x548x215	7,29	18	1200x800x2073	9
06CCTO15S0	MHO 15	546x286x145	0,35	528	1200x800x2168	8
06CCTO21S0	MHO 21	550x375x145	0,44	448	1200x800x2168	8
06CCTO22S0	MHO 22	550x375x145	0,50	336	1200x800x2168	8
06CCTO31S0	MHO 31	546x286x145	0,58	264	1200x800x2168	8
06CCTO32B0	MHO 32B	550x375x191	1,18	160	1200x800x2048	8
06CCTO32S0	MHO 32	550x375x191	1,27	160	1200x800x2048	8
06CCTO33S0	MHO 33	555x550x185	1,64	112	1200x800x2173	8
06CCTO34S0	MHO 34	550x375x191	1,98	80	1200x800x2048	8
06CCTO34A0	MHO 34-A	730x548x215	2,03	72	1200x800x2073	8
06CCTO42S0	MHO 42	730x375x191	1,31	120	1200x800x2048	9
06CCTO44S0	MHO 44	730x375x191	2,42	60	1200x800x2048	9
06CCTO44A0	MHO 44-A	730x375x215	2,56	54	1200x800x2073	9
06CCTO63S0	MHO 63	555x550x185	2,67	56	1200x800x2173	9
06CCTO63A0	MHO 63-A	555x550x215	2,96	48	1200x800x2073	9
06CCTO64S0	MHO 64	550x375x191	3,62	40	1200x800x2048	9
06CCTO64A0	MHO 64-A	730x548x215	3,75	36	1200x800x2073	9
06CCTO66S0	MHO 66	555x550x185	5,21	28	1200x800x2173	9
06CCTO66A0	MHO 66-A	555x550x215	5,44	24	1200x800x2073	9
06CCTO84A0	MHO 84-A	730x375x215	4,15	27	1200x800x2073	9
06CCTO86A0	MHO 86-A	730x548x215	7,29	18	1200x800x2073	9
06CCTF15S0	MHF 15	546x286x145	0,35	528	1200x800x2168	8
06CCTF21S0	MHF 21	550x375x145	0,44	448	1200x800x2168	8
06CCTF22S0	MHF 22	550x375x145	0,50	336	1200x800x2168	8
06CCTF31S0	MHF 31	546x286x145	0,58	264	1200x800x2168	8
06CCTF32B0	MHF 32B	550x375x191	1,18	160	1200x800x2048	8
06CCTF32S0	MHF 32	550x375x191	1,27	160	1200x800x2048	8
06CCTF33S0	MHF 33	555x550x185	1,64	112	1200x800x2173	8
06CCTF34S0	MHF 34	550x375x191	1,98	80	1200x800x2048	8
06CCTF34A0	MHF 34-A	730x548x215	2,03	72	1200x800x2073	8
06CCTF42S0	MHF 42	730x375x191	1,31	120	1200x800x2048	9
06CCTF44S0	MHF 44	730x375x191	2,42	60	1200x800x2048	9
06CCTF44A0	MHF 44-A	730x375x215	2,56	54	1200x800x2073	9
06CCTF63S0	MHF 63	555x550x185	2,67	56	1200x800x2173	9
06CCTF63A0	MHF 63-A	555x550x215	2,96	48	1200x800x2073	9
06CCTF64S0	MHF 64	550x375x191	3,62	40	1200x800x2048	9
06CCTF64A0	MHF 64-A	730x548x215	3,75	36	1200x800x2073	9
06CCTF66S0	MHF 66	555x550x185	5,21	28	1200x800x2173	9
06CCTF66A0	MHF 66-A	555x550x215	5,44	24	1200x800x2073	9
06CCTF84A0	MHF 84-A	730x375x215	4,15	27	1200x800x2073	9
06CCTF86A0	MHF 86-A	730x548x215	7,29	18	1200x800x2073	9



COMBIESTER range



Reference	Designation	Packing dimensions	Unitary weight (kg)	Pallet		Page
				Quantity	Size	
06CCTP32S0	MHP 32	550x375x191	1,6	160	1200x800x2048	8
06CCTP33S0	MHP 33	555x550x185	2,1	112	1200x800x2173	8
06CCTP34S0	MHP 34	550x375x191	2,4	80	1200x800x2048	8
06CCTP63S0	MHP 63	555x550x185	3,1	56	1200x800x2173	9
06CCTP64S0	MHP 64	550x375x191	4,1	40	1200x800x2048	9



06CARP3400	FLANGES TO INCREASE MH34	-	-	-	-	8
06CARP4400	FLANGES TO INCREASE MH44	-	-	-	-	9
06CARP6300	FLANGES TO INCREASE MH63	-	-	-	-	9
06CARP6400	FLANGES TO INCREASE MH64	-	-	-	-	9
06CARP6600	FLANGES TO INCREASE MH66	-	-	-	-	9

ACCESSORIES



Self-extinguishable
polyester
mounting plate

06CAPP2100	PPP MH 21	-	-	-	-	8
06CAPP3100	PPP MH 31	-	-	-	-	8
06CAPP3200	PPP MH 32	-	-	-	-	8
06CAPP3300	PPP MH 33	-	-	-	-	8
06CAPP3400	PPP MH 34	-	-	-	-	8
06CAPP4200	PM MH 42	-	-	-	-	9
06CAPP4400	PM MH 44	-	-	-	-	9
06CAPP6300	PM MH 63	-	-	-	-	9
06CAPP6400	PM MH 64	-	-	-	-	9
06CAPP6600	PM MH 66	-	-	-	-	9
06CAPP8400	PM MH 84	-	-	-	-	9
06CAPP8600	PM MH 86	-	-	-	-	9



Self-extinguishable
bakelite
mounting plate

06CAPB2100	PBQ MH 21	-	-	-	-	8
06CAPB3100	PBQ MH 31	-	-	-	-	8
06CAPB3200	PBQ MH 32	-	-	-	-	8
06CAPB3300	PBQ MH 33	-	-	-	-	8
06CAPB3400	PBQ MH 34	-	-	-	-	8
06CAPB4200	PM MH 42	-	-	-	-	9
06CAPB4400	PM MH 44	-	-	-	-	9
06CAPB6300	PM MH 63	-	-	-	-	9
06CAPB6400	PM MH 64	-	-	-	-	9
06CAPB6600	PM MH 66	-	-	-	-	9
06CAPB8400	PM MH 84	-	-	-	-	9
06CAPB8600	PM MH 86	-	-	-	-	9



metal
mounting plate

06CAPM2100	PM MH 21	-	-	-	-	8
06CAPM3100	PM MH 31	-	-	-	-	8
06CAPM3200	PM MH 32	-	-	-	-	8
06CAPM3300	PM MH 33	-	-	-	-	8
06CAPM3400	PM MH 34	-	-	-	-	8
06CAPM4200	PM MH 42	-	-	-	-	9
06CAPM4400	PM MH 44	-	-	-	-	9
06CAPM6300	PM MH 63	-	-	-	-	9
06CAPM6400	PM MH 64	-	-	-	-	9
06CAPM6600	PM MH 66	-	-	-	-	9
06CAPM8400	PM MH 84	-	-	-	-	9
06CAPM8600	PM MH 86	-	-	-	-	9

References & packaging information

COMBIESTER range



	06CACM1000	BOX + CHASSIS CH10	8
	06CACM2000	BOX + CHASSIS CH20	8
	06CACM3000	BOX + CHASSIS CH30	8
	06CACM4000	BOX + CHASSIS CH40	9
	06CACM6000	BOX + CHASSIS CH60	9
	06CATM000	TC-33	10
	06CATD0100	TCD-33G	10
	06CATD0200	TCD-33A	10
	06CATT0100	TCT-33	10
	06CATL0100	SET KEY	10
	06CABEL0100	BAP	10
	06CABM0100	BFD	10
	06CABD0200	BFM	10
	06CABI0100	BAM	10
	06PEAD0001	DV	10
	06PEAD0002	DVG	10
	06PNAD0002	DEVA	10



06CAFM0100 OF 33 10



06CAFP0100 FP 33 10



Cable sealing boxes

06CACC0100 CCJ-26 10

06CACC0200 CCJ-17 10

06CABP0100 CBP 10



06CAVP3300 MH 33
HINGED GLAZED DOOR 10

06CAVP3400 MH 34
HINGED GLAZED DOOR 10

06CACA1300 CA 135 11

06CACA1800 CA 180 11

06CACA2700 CA 270 11

06CACA3600 CA 360 11

06CACS1300 CA 135 WITHOUT GASKET 11

06CACS1800 CA 180 WITHOUT GASKET 11

06CACS2700 CA 270 WITHOUT GASKET 11

06CACS3600 CA 360 WITHOUT GASKET 11

06CAPF1300 PF 135 11

06CAPF1800 PF 180 11

06CAPF2700 PF 270 11

06CAPF3600 PF 360 11

06CAPS1300 PF 135 WITHOUT GASKET 11

06CAPS1800 PF 180 WITHOUT GASKET 11

06CAPS2700 PF 270 WITHOUT GASKET 11

06CAPS3600 PF 360 WITHOUT GASKET 11



End plates

TPD range



Reference	Designation	Page
0472010	TPD 55	25
0472011	TPD 57	25
0472012	TPD 77	25
0472013	TPD 105	25
0472014	TPD 107	25
0976830-ST	PLACAS 410x410x4	25
0976835-ST	PLACAS 410x660x4	25
0976873-ST	PLACAS 660x660x4	25
0976840-ST	PLACAS 900x410x4	25
0976418-ST	PLACAS 900x660x4	25



MINIPOL range



Reference	Designation	Packing dimensions	Unitary weight (kg)	Pallet		Page
				Quantity	Size	
06PF320001	MN 321	310x261x156	2,2	132	1200x800x2058	14
06PF430001	MN 432	410x311x216	3,7	48	1200x800x1898	14
06PF440001	MN 442	410x410x216	4,6	40	1200x820x1898	14
06PF540001	MN 542	516x411x216	5,5	28	1200x800x1898	14
06PF640001	MN 642	610x411x216	7,5	28	1220x822x1888	15
06PF650001	MN 652	610x510x246	8,2	18	1220x800x1668	15
06PF860001	MN 863	810x610x316	13,1	12	1220x810x2058	15



06PF430002	MN 432/3P	410x311x240	4,0	48	1200x800x2090	14
06PF440002	MN 442/3P	420x420x230	4,7	40	1200x820x2010	14
06PF540002	MN 542/3P	516x412x240	5,9	28	1200x800x2090	14
06PF640002	MN 642/3P	610x411x265	8,0	28	1220x822x2025	15
06PF650002	MN 652/3P	610x510x270	8,8	18	1220x800x1790	15
06PF680002	MN 683/3P	610x810x340	14,0	12	1220x810x2210	15
06PF860002	MN 863/3P	810x610x340	14,0	12	1220x810x2210	15



06PF320002	MN 321-V	-	-	-	-	14
06PF430003	MN 432-V	410x311x216	3,7	48	1200x800x1898	14
06PF440003	MN 442-V	410x410x216	4,6	40	1200x820x1898	14
06PF540003	MN 542-V	516x411x216	5,5	28	1200x800x1898	14
06PF640003	MN 642-V	610x411x216	7,5	28	1220x822x1888	15
06PF650003	MN 652-V	610x510x246	8,2	18	1220x800x1668	15
06PF860003	MN 863-V	810x610x316	13,1	12	1220x810x2058	15




06PF430004	MN 432/3P-V	410x311x240	4,0	48	1200x800x2090	14
06PF440004	MN 442/3P-V	420x420x230	4,7	40	1200x820x2010	14
06PF540004	MN 542/3P-V	516x412x240	5,9	28	1200x800x2090	14
06PF640004	MN 642/3P-V	610x411x265	8,0	28	1220x822x2025	15
06PF650004	MN 652/3P-V	610x510x270	8,8	18	1220x800x1790	15
06PF680004	MN 683/3P-V	610x810x340	14,0	12	1220x810x2210	15
06PF860004	MN 863/3P-V	810x610x340	14,0	12	1220x810x2210	15



06PFPP0001	MN P32	-	-	-	-	14
06PFPP0002	MN P43	-	-	-	-	14
06PFPP0003	MN P44	-	-	-	-	14
06PFPP0004	MN P54	-	-	-	-	14
06PFPP0005	MN P64	-	-	-	-	15
06PFPP0006	MN P65	-	-	-	-	15
06PFPP0007	MN P86	-	-	-	-	15



06PFPM0001	MN PM32	-	-	-	-	14
06PFPM0002	MN PM43	-	-	-	-	14
06PFPM0003	MN PM44	-	-	-	-	14
06PFPM0004	MN PM54	-	-	-	-	14
06PFPM0005	MN PM64	-	-	-	-	15
06PFPM0006	MN PM65	-	-	-	-	15
06PFPM0007	MN PM86	-	-	-	-	15



06PFPP0001	MN PBR32	-	-	-	-	14
06PFPP0002	MN PBR43	-	-	-	-	14
06PFPP0003	MN PBR44	-	-	-	-	14
06PFPP0004	MN PBR54	-	-	-	-	14
06PFPP0005	MN PBR64	-	-	-	-	15
06PFPP0006	MN PBR65	-	-	-	-	15
06PFPP0007	MN PBR86	-	-	-	-	15



06PFPI0001	MN-PI43	-	-	-	-	14
06PFPI0002	MN-PI44	-	-	-	-	14
06PFPI0003	MN-PI54	-	-	-	-	14
06PFPI0004	MN-PI64	-	-	-	-	15
06PFPI0005	MN-PI65	-	-	-	-	15
06PFPI0006	MN-PI86	-	-	-	-	15



CAHORS INTERNATIONAL

ZI de Regourd • CS 90149 • 46003 Cahors cedex 9 - FRANCE

Tel. +33 (0)5 65 35 82 01 • Fax +33 (0)5 65 35 82 14

Email. sales.support@groupe-cahors.com

www.groupe-cahors.com

